



Warrior, Inc.
11100 SW Industrial Way
Tualatin, OR 97062
Phone: (888) 220-6861
Fax: (503) 692-0364
customerservice@warriorproducts.com
www.warriorproducts.com

JEEP WRANGLER MIRROR RELOCATION BRACKETS (WITH MIRRORS)

P/N: 1511 / 1516
INSTALLATION INSTRUCTIONS

IMPORTANT NOTE:

Mirror Relocation Brackets are designed to be used when running no doors or with Warrior Products Adventure Tube Doors. These kits are not compatible with full doors or with half doors using half door uppers.

BRACKET INSTALLATION:

1. The Warrior Mirror Relocation Bracket attaches to the front of your windshield, on the lower part of the windshield hinge.
2. Remove the large bolts on the windshield hinge. Remove one bolt at a time, CAREFULLY, to avoid dropping backing nuts located inside the framework.
3. Mount the Mirror Relocation Bracket using the two (2) stainless steel bolts provided for each side.
4. When finished, be sure to go back and check the tightness of all bolts.
5. Install mirrors into relocation brackets. On YJ and TJ, the nut on the bottom of the mirror holds the mirror into the bracket and is simply unbolted and swapped back and forth easily.
6. On the JK model, this is a torx head bolt instead of a nut. To remove the mirror from the factory mount on the JK you will need to loosen the bolt until it is only slightly threaded and the head of the bolt is protruding below the factory mirror mount.
7. The JK mirror is wedged into place with a taper, much like a steering tie rod end. Do not attempt to lift the mirror out of the mount by hand, you will break the mirror. To free it from the taper tap on the head of the bolt with a mallet upward until the mirror pops free. Remove the bolt and lift the mirror out of the mount.

MIRROR INSTALLATION:

1. Install the mirrors into the brackets by sliding the bottom threaded post of the mirror arm through the tube on the bracket. The threaded portion of the bottom stud will slide thru the hole and be accessible from the bottom of the brackets. Use the provided flat washer and lock nut to attach the mirror to the bracket. Tighten to a snug fit.



WARRIORPRODUCTS.COM





Warrior, Inc.
11100 SW Industrial Way
Tualatin, OR 97062
Phone: (888) 220-6861
Fax: (503) 692-0364

customerservice@warriorproducts.com
www.warriorproducts.com

-
2. Sitting in your driver seat set the mirrors angle to the desired position and lock it into place by tightening the mirror to the bracket securely. Do not over tighten as you may damage your mirrors.
 3. Finish the installation by hand adjusting the mirror lens to your preferred position.
 4. Check tightness of mirror periodically or if you see the mirror begin to vibrate more than normal.

Be sure to check out www.warriorproducts.com for more 100% US Made accessories for your rig.
If you need further assistance installing your product, please contact us by email at customerservice@warriorproducts.com or call us at (888) 220-6861.

THANK YOU FOR PURCHASING WARRIOR PRODUCTS



WARRIORPRODUCTS.COM

