



Warrior, Inc.
11100 SW Industrial Way
Tualatin, OR 97062
Phone: (888) 220-6861
Fax: (503) 692-0364
customerservice@warriorproducts.com
www.warriorproducts.com

JEEP CHEROKEE GEN. 1 STANDARD FRONT BUMPER

P/N: 560 / 56050 / 56051 / 56054 / 56055

INSTALLATION INSTRUCTIONS

PHASE 1 – FACTORY BUMPER REMOVAL:

1. Start by unbolting your bumper on each side. There are 3 bolts in a triangular pattern that hold the bumper in place. Use a 15mm wrench or socket to remove them. If you have factory tow hooks, there will be an additional TORX head bolt further back on the frame rail holding the brackets in place, as well as a bracket on the bottom side of the frame rail.
2. The bumper should now be loose. On the passenger side, there should be a plastic vacuum canister bolted to the bumper from the bottom. Remove the bolts and pull the bumper off of the Jeep. The canister can hang loose while you install your bumper.

PHASE 2 - BUMPER INSTALLATION:

1. If you are also installing a Warrior Products Frame Rail Reinforcement Bracket kit (Part #566), refer to the 566 Instructions at this time. (Note: the 566 Frame Rail Reinforcement Bracket is strongly suggested if you are installing a bumper with D-Rings).
2. If you are not installing the Warrior Products Frame Rail Reinforcement Bracket, please note that there will be additional space between the mounting plates of the bumper and the vehicle body. You may choose to use washers, or some other spacer to fill in the space as needed.
3. Slide your new bumper into place.
4. Using the 3 bolts removed in Phase 1; attach the bumper to the vehicle. Thread all 6 bolts before tightening any of them. Be sure to align the bumper so it is sitting straight on the vehicle as there is some play in the holes. Tighten the mounting hardware evenly working from side-to-side to evenly load both mounting plates on each side.
5. The last part of the installation is to re-attach your vacuum canister. You can either drill holes in the bumper to hold it, or many people choose to relocate it into the engine bay.

If you need further assistance installing your product, please contact us by email at customerservice@warriorproducts.com or call us at (888) 220-6861.

THANK YOU FOR PURCHASING WARRIOR PRODUCTS



WARRIORPRODUCTS.COM





Warrior, Inc.
11100 SW Industrial Way
Tualatin, OR 97062
Phone: (888) 220-6861
Fax: (503) 692-0364
customerservice@warriorproducts.com
www.warriorproducts.com



WARRIORPRODUCTS.COM

