



Warrior, Inc.  
11100 SW Industrial Way  
Tualatin, OR 97062  
Phone: (888) 220-6861  
Fax: (503) 692-0364  
[customerservice@warriorproducts.com](mailto:customerservice@warriorproducts.com)  
[www.warriorproducts.com](http://www.warriorproducts.com)

## **JEEP WRANGLER JK / JKU ROCK CRAWLER REAR BUMPER**

*P/N: 592 / 593*

### **INSTALLATION INSTRUCTIONS**

#### **FACTORY BUMER REMOVAL:**

1. Removing two 16mm bolts on either side of the frame rail.
2. The factory rear bumper will also have two braces bolted to the underside of the rear cross member. Remove and discard these braces and hardware as they are no longer needed.
3. On factory hitch equipped vehicles, the bumper may need to be slightly modified to clear the wiring plug bracket. Alternatively, the wiring plug bracket may be removed altogether.

#### **BUMPER INSTALLATION:**

1. Set bumper in place and bolt into location with factory hardware. Ensure the bumper is aligned and level.
2. Tighten bolts.
3. If you have the d-ring version, you can install your d-ring shackles now.

If you need further assistance installing your product, please contact us by email at [customerservice@warriorproducts.com](mailto:customerservice@warriorproducts.com) or call us at (888) 220-6861.

**THANK YOU FOR PURCHASING WARRIOR PRODUCTS**



**WARRIORPRODUCTS.COM**

